

# CleanMaster

TANKS FOR STORAGE AND DISTRIBUTION  
OF WINDSHIELD WASHER FLUID



**TITAN**®

▶ SAFE AND FUNCTIONAL SOLUTION

# CleanMaster

AN IDEAL SOLUTION FACILITATING STORAGE AND DISTRIBUTION OF WINDSHIELD WASHER FLUID WITH SIMULTANEOUS CONTROL OF THE DISPENSED SUBSTANCE

## ADVANTAGES

- › Resistance to changeable weather conditions.
- › Tested dispensing system.
- › Sturdy and simple design.
- › Capacities ranging from 1300 to 5000 litres.
- › The tank does not require frequent maintenance procedures.
- › 5-year warranty on tank tightness, 2-year warranty on equipment. Warranty covers products used in accordance with the manufacturer's recommendations.

## AVAILABLE CAPACITIES AND DIMENSIONS:



**PRODUCT CODE**  
OCM01300WH\*

**Capacity** | 1300 l  
**Diameter** | 1.20 m  
**Height** | 1.40 m



**PRODUCT CODE**  
OCM03500WH\*

**Capacity** | 3500 l  
**Diameter** | 1.90 m  
**Height** | 1.80 m



**PRODUCT CODE**  
OCM02500WH\*

**Capacity** | 2500 l  
**Diameter** | 1.65 m  
**Height** | 1.50 m



**PRODUCT CODE**  
OCM05000WH\*

**Capacity** | 5000 l  
**Diameter** | 2.01 m  
**Height** | 2.30 m

\* The remaining part of the code depends on the specifications of the tank.  
Warranty: tank tightness 5 years, tank equipment 2 years.

## STANDARD EQUIPMENT

- › Single-walled white semi-transparent tank.
- › Inspection hatch 8".
- › Vent connector.
- › Filling unit 2" (at the top of the container).
- › A simplified dispensing system consists of a submersible pump 230V (ON/OFF switch), a manual nozzle and a 6m dispensing hose.

## OPTIONAL ACCESSORIES

- › Dry-clutch 2" connection for filling the tank from the top.
- › Filling line from the top of the tank to the working level with a dry clutch 2".
- › Digital flowmeter at the nozzle.
- › Automatic nozzle.
- › Dial level indicator.
- › Clock level gauge.

## ELEMENTS OF TANK EQUIPMENT



› Submersible pump.

› Level gauge.

› Digital flowmeter.

The exact hues of the colours presented in the flyers may differ, depending on the quality of print.  
Product specifications may be slightly modified; to obtain an up-to-date equipment specification, contact the office or the nearest distributor.

Distributor: