

The new DESO 200 & DESO 300 tanks are a market novelty among mobile solutions for diesel storage and distribution. Refueling vehicles anywhere you need has never been so easy!



5-year tank warranty







Specification:

- 1. Single skin tank with a capacity of 200/300 litres
- 2. 1" suction hose with mesh filter
- 3. PIUSI 12/24 V DC pump (max flow rate 50 l/min)
- 4. 6 m pump's power cable with clamps
- 5. 4 m distribution hose (3/4")
- 6. Nozzle
- 7. Digital flow meter PIUSI K24 (optional)
- 8. Fuel cap
- 9. Air vent

5-year tank warranty and 2-year equipment warranty



Product	Product code	Capacity [1]	Width [mm]	Length [mm]	Height [mm]	Equipment
DESO 200	OTMD0200GG_12	200	600	800	610	12 V pump
	OTMD0200GG_12_K24	200	600	800	610	12 V pump + flow meter
DESO 300	OTMD0300GG_12	300	600	800	890	12 V pump
	OTMD0300GG_12_K24	300	600	800	890	12 V pump + flow meter

All dimensions are approximate. The dimensions may vary due to manufacturing process variations and/or environmental conditions.

The producer takes every care and precaution to ensure that the information in this document is accurate at the point of publishing. However, due to continuous product development, specifications are subject to change and the details given in this document may no longer be correct. To obtain an up-to-date equipment specification or technical documentation, contact the office or the nearest distributor. All rights reserved.