



Ø200 cover PVC	A Ø160 cover Cast iron 40t	B Ø400 cover PVC	C Ø315 cover Cast iron 40t	D Ø760 cover PE	E Ø630 cover Cast iron 40t	F

Volume V (m3)	Length L (mm)	Product code
8	4370	501608
10	5410	501610
12	6360	501612
15	7860	501615
17	8850	501617
20	10360	501620
22	11340	501622
25	12860	501625

Pos.	Description	Material	Size
1	Cover	PVC / PE / Cast iron	according to selection
2	Service opening	PE100	according to selection
3	Tank cylinder, double wall	PE100	ID1600, SN2
4	End cap	PE	ID1600
5	Inlet coupling	PVC	according to selection
6	Alarm device Tank-Check RF-412	-	optional

Tank volume	V =	m ³
Inlet depth from Ground Surface NB! max 1,2m	H =	mm / standard 950 mm <input type="checkbox"/>
Inlet diameter	D110 <input type="checkbox"/> D160 <input type="checkbox"/>	
Service opening type	A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D <input type="checkbox"/> E <input type="checkbox"/> F <input type="checkbox"/>	
Service opening location	L1 =	mm / middle <input type="checkbox"/>
Alarm device	<input type="checkbox"/> YES / NO <input type="checkbox"/>	

Drawn:			
Approved:			
Mass: kg	Product code:	Rev.	
NA	5016 / ordersheet	0	